

Appl. No. 10/632,257

Reply to Office Action of September 23, 2005

IN THE CLAIMS

Applicant respectfully declines to amend the claims at this time. All pending claims are listed below.

1. (Previously Amended) A method of thermal management in a voltage source inverter, the method comprising:

sensing a low output frequency condition corresponding to zero or low voltage across phases in the voltage source inverter while the voltage source inverter is receiving a constant DC link voltage;

determining a zero vector modulation responsive to the sensed low output frequency condition; and

applying the determined zero vector modulation to reduce thermal stress in the voltage source inverter.

2. (Original) The method of claim 1, wherein determining the zero vector modulation responsive to the sensed low output frequency condition comprises:

mapping an output voltage requirement to a space vector structure; and

determining state switching space vectors based on the mapped output voltage requirement.

3. (Original) The method of claim 2, wherein the magnitude of a combination of state switching space vectors is equal to the magnitude of the output voltage requirement.

Appl. No. 10/632,257

Reply to Office Action of September 23, 2005

4. (Original) The method of claim 2, wherein determining the state switching space vectors comprise:

determining active state switching space vectors associated with the state switching space vectors;

determining duty cycles for the active state switching space vectors based on the active state switching space vectors and the mapped output voltage requirement; and

determining a duty cycle for at least one zero state switching space vector based on the determined duty cycles of the active state switching space vectors and a switching period.

5. (Original) The method of claim 4, wherein the duty cycle for the at least one zero state switching space vectors is selected from the group consisting of: a first zero state duty cycle, a second zero state duty cycle, and a combination of the zero state duty cycles.

6. (Original) The method of claim 1, wherein applying the determined zero vector modulation to reduce thermal stress in the voltage source inverter comprises:

applying a net voltage from the inverter to a load when active state switching space vectors are utilized; and

applying a shorted voltage from the inverter to the load when zero state switching space vectors are utilized.

7. (Withdrawn) A computer readable medium storing a computer program comprising:

computer readable code for determining a zero vector modulation responsive to a low output frequency condition; and

computer readable code for applying the determined zero vector modulation to reduce thermal stress in the voltage source inverter.

Appl. No. 10/632,257

Reply to Office Action of September 23, 2005

8. (Withdrawn) The computer readable medium of claim 7, wherein the computer readable code for determining a zero vector modulation responsive to the sensed low output frequency condition comprises:

computer readable code for mapping an output voltage requirement to a space vector structure; and

computer readable code for mapping an output voltage requirement to a space vector structure; and

computer readable code for determining state switching space vectors based on the mapped output voltage requirement.

9. (Withdrawn) The computer readable medium of claim 8, wherein the magnitude of a combination of state switching space vectors is equal to the magnitude of the output voltage requirement.

10. (Withdrawn) The computer readable medium of claim 8, wherein the computer readable code for determining the switching space vectors comprises:

computer readable code for determining active state switching space vectors associated with the state switching space vectors;

computer readable code for determining duty cycles for the active state switching space vectors based on the active state switching space vectors and the mapped output voltage requirement; and

computer readable code for determining a duty cycle for at least one zero state switching space vector based on the determined duty cycles of the active state switching space vectors and a switching period.

11. (Withdrawn) The computer readable medium of claim 8, wherein the duty cycle for the at least one zero state switching space vectors is selected from the group consisting of: a first zero state duty cycle, a second zero state duty cycle, and a combination of the zero state duty cycles.

Appl. No. 10/632,257

Reply to Office Action of September 23, 2005

12. (Withdrawn) The computer readable medium of claim 7, wherein the computer readable code for applying the determined zero vector modulation to reduce thermal stress in the voltage source inverter comprises:

computer readable code for applying a net voltage from the inverter to a load when active state switching space vectors are utilized; and

computer readable code for applying a shorted voltage from the inverter to the load when zero state switching space vectors are utilized.

13. (Previously Amended) A system for thermal management in a voltage source inverter, the system comprising:

means for sensing a low output frequency condition corresponding to zero or low voltage across phases in the voltage source inverter while the voltage source inverter is receiving a constant DC link voltage;

means for determining a zero vector modulation responsive to the sensed low output frequency condition; and

means for applying the determined zero vector modulation to reduce thermal stress in the voltage source inverter.